

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7; & 12 T29-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10621)

Set a conglomerate stone 20x12x6", 15" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A pine, 36" dia., bears N.58°E., 19 lks., mkd: ¼ S7 BT.
 A fir, 15" dia., bears N.6°W., 29 lks., mkd: ¼ S12 BT.
No iron post available for this corner.

U.S. Forest Service, Tiller Ranger District - 4/5/1961 (Filed Dec. 5, 1973) - C.S. File 56/40-63

Found - Stone marked on west face.
Note - Best route to reach cor. use FS RD. No. 2942

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debby Stewart, witness - July 21, 1981 - C.S. File 61/27-24

Found - 16x12x5" stone protruding 4" out of the ground (rec. is 20x12x6"). The West face had faint marks on it, but I could not positively identify a 1/4.
BTs - 36" Pine (Orig.) stump badly decayed except for the scribed face which read ¼ S7 BT bears N.58°E., 12.5 ft.
 15" Fir (orig. 15") snag, 10 ft. tall, badly decayed with healed over blaze bears N.6°W., 19.1 ft.
Set - I referenced out the center of stone and set a Brass Cap protruding 5" marked Douglas Co. Surveyor T29S R1E S12 S7 R2E 1981, in its place. I place orig. stone along west side of B.C. & flush with the ground.
New BTs- 14" Fir bears S.22°E., 19.5 ft., scribed ¼ S7 CS BT.
 15" Pine bears S.10°W., 17.0 ft. scribed ¼ S12 CS BT
 16" Fir bears S.48°W., 54.7 ft., scribed ¼ S12 CS BT.
 17" Fir bears N.65°W., 31.7 ft., scribed ¼ S12 CS BT
NOTE - All trees have new DCSO BT tags.
NOTE - All new BT's are scribed with double blazes.
NOTE - Both orig. BT stumps are approx. 6-ft. Southerly of Rd.#2942.