

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Cor. Secs. 6, 7; 1 & 12 T29-01E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol 25 Pages 10621-2)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T29S
R1E|R2E
S 1|S 6
S 12|S 7
1921

from which

- A fir, 12" dia., bears N.83°E., 35 lks mkd: T29S R2E S6 BT
- A fir, 10" dia., bears S.83°E., 37 lks mkd: T29S R2E S7 BT
- A fir, 9" dia., bears S.24°W., 45 lks mkd: T29S R1E S12 BT
- A fir, 24" dia., bears N.60°W., 90 lks mkd: T29S R1E S1 BT

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Gary Commons - July 31, 1974 - C.S. File 57/2-7

Found - 1921 U.S. GLO brass cap properly mkd. from which:
A Fir orig. 12" now 20", bears N.83°E., 23.1 ft. blaze well-healed.
A Fir orig. 10" now 14", bears S.83°E., 24.4 ft. blaze well-healed.
A Fir, orig. 9" now 14" bears S.24°W., 29.7 ft. blaze well-healed.
A Fir, orig. 24" now 25" bears N.60°W., 59.4 ft.
No new BTs marked at this time.