

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10762-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T29S		R2E
S 7		S 8
S 18		S 17
1926		

from which

- A D.Fir, 10" dia., bears N.38°E., 29 lks., mkd: T29S R2E S8 BT.
- A D.Fir, 14" dia., bears S.22°E., 25 lks., mkd: T29S R2E S17 BT.
- A D.Fir, 12" dia., bears S.51°W., 27 lks., mkd: T29S R2E S18 BT.
- A D.Fir, 14" dia., bears N.14°W., 25 lks., mkd: T29S R2E S7 BT.