

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6; 31 & 32 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 24 & 25 Page(s) 10362-3 & 10699-700 (duplicate))

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 5, 6, 31, & 32, with brass cap mkd

T28S|R2E  
S 31|S 32  
S 6|S 5  
T29S  
1926

from which

- A D.Fir, 12" dia., bears N.59°E., 98 lks., mkd: T28S R2E S32 BT.
- A yew, 10" dia., bears S.30°E., 27½ lks., mkd: T29S R2E S5 BT.
- A hemlock, 10" dia., bears S.58½°W., 31 lks., mkd: T29S R2E S6 BT.
- A S.Pine, 36" dia., bears N.54°W., 87 lks., mkd: T28S R2E S31 BT.