

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10745)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd

T29S	R2E
S 20	S 21
S 29	S 28
1923	

from which

- A D.Fir, 32" dia., bears N.53°E., 46 lks., mkd: T29S R2E S21 BT.
- A D.Fir, 10" dia., bears S.42°E., 17 lks., mkd: T29S R2E S28 BT.
- A D.Fir, 12" dia., bears S.72°W., 23 lks., mkd: T29S R2E S29 BT.
- A D.Fir, 24" dia., bears N.41°W., 28 lks., mkd: T29S R2E S20 BT.