

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION WC Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10747)

N.0°3'W., bet. secs. 20 & 21

78.56 chs

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for witness corner to the corner of secs. 16, 17, 20, & 21, with brass cap mkd

WC	
T29S	R2E
<u>S 17</u>	<u>S 16</u>
S 20	S 21
1926	

from which

- A cedar, 14" dia., bears N.28°E., 33 lks., mkd: WC T29S R2E S21* BT. (Should be S16?)
- A D.Fir, 26" dia., bears S.25°E., 22 lks., mkd: WC T29S R2E S21 BT.
- A cedar, 6" dia., bears S.65°W., 17½ lks., mkd: WC T29S R2E S20 BT.
- A D.Fir, 18" dia., bears N.8½°W., 46 lks., mkd: WC T29S R2E S20* BT. (Should be S17?)

* per BLM orig. line notes

80.00 chs

Point for cor. of secs. 16, 17, 20, & 21, falls on steep bare face of rock where it is impracticable to build a permanent monument; or to make a lasting and conspicuous mark, though not entirely inaccessible.