

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10749-50)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T29S	R2E
S 8	S 9
S 17	S 16

1926

from which

- A cedar, 28" dia., bears N.43½°E., 16 lks., mkd: T29S R2E S9 BT.
- A cedar, 24" dia., bears S.72°E., 29 lks., mkd: T29S R2E S16 BT.
- A D.Fir, 24" dia., bears S.41°W., 79 lks., mkd: T29S R2E S17 BT.
- A D.Fir, 32" dia., bears N.55°W., 50 lks., mkd: T29S R2E S8 BT.