

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor Secs 33, 34; 3, & 4 T30-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10687-8 & Vol. 26 Page(s) 11147-8)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T29S R2E
S 33|S 34
S 4|S 3
T30S
1923

from which

- A fir, 26" dia., bears N.62°E., 6 lks., mkd: T29S R2E S34 BT.
- A fir, 36" dia., bears S.28°E., 88 lks., mkd: T30S R2E S3 BT.
- A fir, 12" dia., bears S.68°W., 29 lks., mkd: T30S R2E S4 BT.
- A fir, 14" dia., bears N.5°W., 7 lks., mkd: T29S R2E S33 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21855)

The cor. of secs. 3, 4, 33, & 34, which is an iron post, 2" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.