

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 3 T30-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10687 & Vol. 26 Page(s) 11147)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 34}{S\ 3}$
1923

from which

- A fir, 28" dia., bears N.28°E., 29 lks., mkd: 1/4 S34 BT.
- A maple, 10" dia., bears S.42°E., 28 lks., mkd: 1/4 S3 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21855)

The 1/4 sec. cor. of secs. 3 & 34, which is an iron post, 1" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.