

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor. Secs. 34, 35; 2, & 3 T30-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10686 & Vol. 26 Page(s) 11146-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd

T29S R2E  
S 34 | S 35  
S 3 | S 2  
T30S  
1923

from which

- A hemlock, 18" dia., bears N.28°E., 28 lks., mkd: T29S R2E S35 BT.
- A hemlock, 10" dia., bears S.26°E., 36 lks., mkd: T30S R2E S2 BT.
- A hemlock, 9" dia., bears S.75°W., 27 lks., mkd: T30S R2E S3 BT.
- A hemlock, 12" dia., bears N.52°W., 17 lks., mkd: T29S R2E S34 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21854)

-----  
The cor. of secs. 2, 3, 34, & 35, which is an iron post, 2" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.