

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10720)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd

T29S	R2E
S 27	S 26
S 34	S 35
1923	

from which

- A pine, 40" dia., bears N.35°E., 45 lks., mkd: T29S R2E S26 BT.
- A cedar, 24" dia., bears S.24°E., 35 lks., mkd: T29S R2E S35 BT.
- A cedar, 28" dia., bears S.47°W., 88 lks., mkd: T29S R2E S34 BT.
- A fir, 48" dia., bears N.57°W., 12 lks., mkd: T29S R2E S27 BT.