

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10724)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 14, 15, 22, & 23, with brass cap mkd

T29S	R2E
S 15	S 14
S 22	S 23
1923	

from which

- A cedar, 20" dia., bears N.89°E., 15 lks., mkd: T29S R2E S14 BT.
- A D.Fir, 20" dia., bears S.55°E., 59 lks., mkd: T29S R2E S23 BT.
- A D.Fir, 15" dia., bears S.33½°W., 27½ lks., mkd: T29S R2E S22 BT.
- A D.Fir, 15" dia., bears N.15½°W., 65 lks., mkd: T29S R2E S15 BT.