

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3; 34, & 35 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 24 & 25 Pages 10366-7 & 10703 (duplicate))

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd

T28S|R2E  
S 34|S 35  
S 3|S 2  
T29S  
1926

from which

- A D.Fir, 14" dia., bears N.82°E., 55 lks., mkd: T28S R2E S35 BT.
- A D.Fir, 10" dia., bears S.13°E., 46 lks., mkd: T29S R2E S2 BT.
- An I.Cedar, 20" dia., bears S.37½°W., 32 lks., mkd: T29S R2E S3 BT.
- A D.Fir, 12" dia., bears N.74°W., 35 lks., mkd: T28S R2E S34 BT.