

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10686 & Vol. 26 Page(s) 11146)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 35}{S\ 2}$
1923

from which

A maple, 22" dia., bears N.16°W., 27 lks., mkd: 1/4 S35 BT
A fir, 30" dia., bears S.43°E., 39 lks., mkd: 1/4 S2 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page 21854)

The 1/4 sec. cor. of secs. 2 & 35, which is an iron post, 1" dia., 10" above ground, firmly set, with brass cap (properly) mkd.

from which

A fir, 40" dia., bears N.68°E., 11 lks., mkd: 1/4 S35 BT.
(Old BT) [6/4/2012 DCSO: doesn't agree w/1923 rec]
A fir, 17" dia., bears S.68°W., 24 lks., mkd: 1/4 S2 BT.
(Old BT) [6/4/2012 DCSO: doesn't agree w/1923 rec]