

PRIMARY CORNER DESCRIPTION Cor. Secs. 35, 36; 1, & 2 T30-2E

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10685 & Vol. 26 Page(s) 11145)

 Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd

T29S	R2E
S 35	S 36
S 2	S 1
T30S	
1923	

from which

- A madrona, 6" dia., bears N.66°E., 10 lks., mkd: T29S R2E S36 BT.
- A madrona, 7" dia., bears S.43°E., 34 lks., mkd: T30S R2E S1 BT.
- A madrona, 6" dia., bears S.29°W., 6 lks., mkd: T30S R2E S2 BT.
- A madrona, 12" dia., bears N.66°W., 5 lks., mkd: T29S R2E S35 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Pages 21853-4)

 The cor. of secs. 1, 2, 35, & 36, which is an iron post, 2" dia 10" above ground firmly set with brass cap (properly) mkd

- A madrona, 7" dia., bears N.66°E., 10 lks., mkd: T29S R2E S36 BT. (Old BT)
- A madrona, 7" dia., bears S.43°E., 34 lks., mkd: T30S R2E S1 BT. (old BT)
- A madrona, 6" dia., bears S.29°W., 6 lks., mkd: T30S R2E S2 BT. (old BT)
- A madrona, 12" dia., bears N.66°W., 5 lks., mkd: T29S R2E S35 BT. (Old BT)
- A fir, 47" dia., bears N.34°E., 95 lks., mkd: T29S R2E S36 BT. (New BT)
- A fir, 22" dia., bears S.21°E., 71 lks., mkd: T30S R2E S1 BT. (New BT)
- A fir, 28" dia., bears S.17°W., 97 lks., mkd: T30S R2E S2 BT. (New BT)
- A fir, 30" dia., bears N.61°W., 89 lks., mkd: T29S R2E S35 BT. (New BT)