

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10714-5)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd

| | |
|------|------|
| T29S | R2E |
| S 11 | S 12 |
| S 14 | S 13 |
| 1926 | |

from which

- A D.Fir, 5" dia., bears N.26¼°E., 49½ lks., mkd: T29S R2E S12 BT.
- A D.Fir, 32" dia., bears S.1°E., 100 lks., mkd: T29S R2E S13 BT.
- A S.Pine, 48" dia., bears S.73°W., 39 lks., mkd: T29S R2E S14 BT.
- A D.Fir, 5" dia., bears N.29°W., 31 lks., mkd: T29S R2E S11 BT.