

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10716-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T29S	R2E
S 2	S 1
S 11	S 12
1926	

from which

- A hemlock, 12" dia., bears N.2°E., 42 lks., mkd: T29S R2E S1 BT.
- A hemlock, 18" dia., bears S.15°E., 40 lks., mkd: T29S R2E S12 BT.
- A hemlock, 8" dia., bears S.55°W., 21 lks., mkd: T29S R2E S11 BT.
- A W.Fir, 10" dia., bears N.64½°W., 37 lks., mkd: T29S R2E S2 BT.