

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 36 & 1 T30-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10685 & Vol. 26 Page(s) 11145)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 36}{S\ 1}$
1923

from which

- A fir, 18" dia., bears N.48°W., 28 lks., mkd: 1/4 S36 BT.
- A fir, 12" dia., bears S.22°E., 32 lks., mkd: 1/4 S1 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21853)

The 1/4 sec. cor. of secs. 1 & 36, which is an iron post, 1" dia., 6" above ground, firmly set, mkd. and witnessed as described in the official record.