

PRIMARY CORNER DESCRIPTION SE Tsp Corner

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 26 Page(s) 11144)

Set an iron post, 3 ft. long, 3" dia., 27" in the ground, for cor. of Tps. 29 & 30 S., Rs. 2 and 3 E., with brass cap mkd:

T29S	
R2E	R3E
S 36	S 31
S 1	S 6
T30S	
1923	

from which

- A pine, 36" dia., bears N.34°E., 23 lks., mkd: T29S R3E S31 BT.
- A chincapin, 9" dia., bears S.67°E., 60 lks., mkd: T30S R3E S6 BT.
- A pine, 46" dia., bears S.80°W., 41 lks., mkd: T30S R2E S1 BT.
- A chincapin, 12" dia., bears N.38°W., 20 lks., mkd: T29S R2E S36 BT.

Fd. & Used on GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11053-4)

Fd. & used on GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21853)

Maurice "Ed" Farr, USFS - Nov. 18, 1986 - C.S. File 62/33-6

Found - 1923 GLO 3" iron post, firmly set projecting 6" above ground with a 3¼" brass cap, properly mkd. 38" S.Pine, N.34°E., 15.2 ft. with a healed blaze. 48" S.Pine stump S.80°W., 27.1 ft. with scribe marks "T30S R2E" visible on an opened blaze.

A roothole, N.38°W., 13.2 ft. with an 8" chinquapin log alongside with scribe marks "T29S R2E S36 BT" visible on a partially healed blaze.

New BTs- A 5" W.Fir, S.55°E., 23.0 ft. scribed "X" on a chest high blaze and "BT" on a low blaze.

A 6" W.Fir, S.11¼°W., 24.4 ft. scribed "T30S R2E S1 BT" on a single blaze.

A 14" D. Fir, N.45°W., 26.1 ft. scribed "T29S R2E S36 BT" on a single blaze

continued next page

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Tsp Corner

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

I set a 6 ft. steel fence post, driven 2 ft. in the ground as a guard post, bears N.08°W., 2.0 ft. with Forest Service sign No.54-4 attached.
All new BTs have a 3/4" brass washer, stamped "LS 1181" nailed flush to the base of the blaze.
Due to the proximity of the guard post I find the magnetic declination to be 12°E.
The corner is 5.0 mi. up Forest Road No2947-300 (0.1 mi. past road No.2947-365) and is about 65 ft. north of the road. This corner is on the boundary of the Rogue-Umpqua Divide Wilderness.