

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 30, T29-03E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10692-3)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 25|S 30
1923

from which

- A fir, 20" dia., bears S.62°E., 37 lks., mkd: 1/4 S30 BT.
- A fir, 40" dia., bears N.71°W., 38 lks., mkd: 1/4 S25 BT.

Stephan L. Barott - For: Umpqua Nat'l Forest - Nov. 1998/June 1999 - M 133-13

Found - A 2 1/2" dia., brass cap on a 1" dia., iron pipe protruding 6" above ground, mkd:

US GENERAL LAND OFFICE SURVEY
T 29 S
S 25|S 30
1923

A 41" dia., D.Fir bears S.63°34'E., 25.4 ft. with a healed blaze. (Rec. S.62°E., 24.4 ft.)

A Fir stump, size indeterminate, bears N.70°14'W., 21.9 ft. with no marks visible. (Rec. N.71°W., 25.1 ft.)

Set - A 9" dia., Cedar bears S.40°34'W., 43.8 ft., mkd: 1/4S25BT, with a brass washer stamped LS2332 attached.