

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10694)

 Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd

T29S	
R2E	R3E
S 13	S 18
S 24	S 19
1923	

from which

- A fir, 26" dia., bears N.85°E., 43 lks., mkd: T29S R3E S18 BT.
- A fir, 10" dia., bears S.43°E., 21 lks., mkd: T29S R3E S19 BT.
- A fir, 9" dia., bears S.82°W., 41 lks., mkd: T29S R2E S24 BT.
- A cedar, 16" dia., bears N.35°W., 31 lks., mkd: T29S R2E S13 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10773)

 The cor. established for secs. 13, 18, 19, & 24, which is an iron post 2" in dia., 10" above the ground, with brass cap marked & witnessed as described in the field notes of the orig. survey. I obliterate all marks on E side of brass cap and on BTs E of line, & remark brass cap.

T29S	
S 13	T29S
S 24	R3E
R2E	S 19
1923	

from which the orig. BTs

- A fir, 9" dia., bears S.82°W., 41 lks., mkd: T29S R2E S24 BT.
- A cedar, 16" dia., bears N.35°W., 31 lks., mkd: T29S R2E S13 BT.