

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10694-5)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 13 | S 18
1923

from which

- A fir, 8" dia., bears S.60°E., 21 lks., mkd: 1/4 S18 BT.
- A fir, 6" dia., bears S.66°W., 18 lks., mkd: 1/4 S13 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10774)

The 1/4 sec. cor. established for secs. 13 & 18, which is an iron post, 1" in dia., 10" above the ground, with brass cap marked & witnessed approximately as described in the field notes of the orig. survey. I obliterate all marks on the E side of the brass cap and on the BT E of line, and mark a new BT W of line, from the cor.

- A fir (New), 5" dia., bears S.34°W., 26 lks., mkd: 1/4 S13 BT.
- A fir (old), 8" dia., bears S.65°W., 21 lks., mkd: 1/4 S13 BT.

This cor. will hereafter refer to sec. 13 only