

PRIMARY CORNER DESCRIPTION Cor. Secs. 12 & 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10695-6)

 Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T29S	
R2E	R3E
S 12	S 7
S 13	S 18
1926	

from which

- A W.Fir, 16" dia., bears N.70½°E., 42 lks., mkd: T29S R3E S7 BT.
- A R.Cedar, 10" dia., bears S.42°E., 27 lks., mkd: T29S R3E S18 BT.
- A D.Fir, 36" dia., bears S.63°W., 39 lks., mkd: T29S R2E S13 BT.
- A W.Fir, 30" dia., bears N.41°W., 67 lks., mkd: T29S R2E S12 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10775)

 The cor. established for secs. 7, 12, 13 & 18, which is an iron post, 2" in dia 12" above the ground, with brass cap mkd & witnessed as described in the field notes of the original survey. I obliterate all marks on E. side of the cap and on bearing trees E. of the line, and remark brass cap as follows

T29S	
S 12	T29S
S 13	R3E
R2E	S 18
1926	

from which the orig. BTs

- A Fir, 36" dia., bears S.63°W., 39 lks., mkd: T29S R2E S13 BT.
- A Fir, 30" dia., bears N.41°W., 67 lks., mkd: T29S R2E S12 BT.

This cor. will hereafter refer to sec. 12 & 13 only