

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10696)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 12 | S 7  
1926

from which

- A S.Pine, 36" dia., bears S.35°E., 90 lks., mkd: 1/4 S7 BT.
- A W.Fir, 32" dia., bears S.31°W., 24 lks., mkd: 1/4 S12 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10776)

-----  
The 1/4 sec. cor. established for sees. 7 & 12, which is an iron post 1" in dia., 12" above the ground, with brass cap marked and witnessed as described in the field notes of the original survey. I obliterated all marks on the E side of the brass cap and on bearing trees E of the line, and mark a new bearing tree W of the line, from the cor.

- A fir, (old) 34" in dia., bears S.39°W.. 84 lks. mkd 1/4 S12 BT.
- A Fir (new) 16" in dia., bears N.19°W., 40 lks., mkd 1/4 S12 BT.

This cor. will hereafter refer to secs. 12 only.