

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 992010

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES #192

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 192 by Frederick W. Rase, surveyor, under special instructions dated Feb. 29, 1916 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12068)

Set a quartzite stone, 24x15x12", 14" in the ground, over a stone mkd. with a cross for cor. No. 1 of this survey, mkd. 1 HES 192 on side facing the claim from which
 A pine, 14" dia., bears N.6°13'E., 14, lks., mkd. X 1 HES 192 BT
 A pine, 14" dia., bears S.16°00'W., 26 lks. mkd X 1 HES 192 BT
Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.
U.S.L.M. No. 192 bears N.78°47'W., 3.80 ohs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Dec. 1969 - C.S. File 54/96-23

Found - Old Corner Stone, in place & mkd: "+" on top and "1 HES 192"
 Orig. 14", now 28" Pine, alive, N.6¼°E. 9.2 ft., shows scar, we Tag.
 Hole in ground where other Orig. BT, stood.
Set - Brass Cap at Cor. mkd: County Surveyors T29S R2E (Reset Stone alongside) Office, 1969 COR #1<HES 192
New BTs- 14" D.Fir S.81°W. 12.9 ft. mkd: "1 HES 192 CS BT"
 9" Cedar N.54°E. 11.1 ft. mkd: "1 HES 192 CS BT"
This corner lies on flat, gently sloping N. E.
Note - The Old Corner Stones set for the corners of this Homestead Entry Survey #192 are marked with small and hard to find numbers and letters.

Fd. old healed blaze below CS blaze (SW BT) 3/1981 - C.S. File 61/19-21