

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 992060

PRIMARY CORNER DESCRIPTION Cor. No. 6 HES #192

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 192 by Frederick W. Rase, surveyor, under special instructions dated Feb. 29, 1916 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12070

Set a lava stone, 24x10x8", 14" in the ground, over a stone mkd. with a cross for cor. No. 6 of this survey, mkd. 6 HES 192 on side facing the claim; from which
 A fir, 16" dia., bears S.12°45'W., 72 lks., mkd. X 6 HES 192 BT.
 A fir, 16" dia., bears S.84°20'W., 22 lks., mkd. X 6 HES 192 BT.
Raise a mound of earth, 4 ft. base, 2 ft. high, 31 ft. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Dec. 1969 - C.S. File 54/96-28

Found - Old Corner Stone, in place, mkd: "6 HES192" on claim side.
 Orig. 16", now 30" Fir, alive, S.12¾°W. 47.5 ft., shows good scar, we tag.
 Orig. 16", now 24" Fir, alive, S.84⅓°W. 14.5 ft., shows good scar, we tag.
Set - Brass Cap at Cor. mkd: County Surveyors T29S R2E (Reset stone alongside) Office, 1969 Cor.#6< HES 192
New BTs- 7" D.Fir N.45½°W. 25.4 ft. mkd: "6 HES 192 CS BT".
 8" D.Fir S.30°E. 23.0 ft. mkd: "6 HES 192 CS BT".
This corner lies on moderate, southwest slope.
Note - The Old Corner Stones set for the corners of this Homestead Entry Survey #192 are marked with small and hard to find numbers and letters.

Fd. OK 3/1981 - C.S. 61/19-21