

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100106

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only, T29-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6321)

Set Fir post for ¼ sec. cor., from which
A Fir tree 36" dia., bears S.65°E., 17 lks.
A Fir tree 30" dia., bears S.15°W., 16 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6203-04 and (duplicate Pgs. 6826-27, Vol. 16)

The old ¼ sec. cor. in E. bdy. Sec. 36 is nearly obliterated. No trace remains of the post and the marks on the bearing trees are defaced. I re-establish the cor. in its original position as the ¼ sec. cor. in E. bdy. Sec. 36, T29S R3W only as follows
Set a slate stone 18x15x10 ins., 10 ins. in the ground for ¼ sec. cor., marked ¼ on W. face, from which
A Fir 30" dia., bears S.15°W., 18 lks. mkd. ¼ S36 BT
A Madrone 20" dia., bears N.59°W., 70 lks. mkd. ¼ S36 BT.

GLO resurvey by Elmer Strickler, U.S. Transitman under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6223-24)

Intersect the ¼ cor. of E. bdy. of sec. 36, which is a slate stone, firmly set, marked and witnessed as described by the surveyor general.

BLM resurvey by Peter Peterson and Daniel Berry under Group #749, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14917-8)

The ¼ sec. cor. of sec. 36 only, remonumented by Mensch in 1908, with a slate stone, 18x15x10", firmly set, 10" in the ground, mkd ¼ on W face, from which the BTs marked by Mensch
A fir, 42" dia., bears S.15°W., 18 lks., with healed blaze.
A madrone, stump, 30" dia bears N.59°W., 70 lks., with healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked

 S 36
 T 29S
 R 3 W
 1971

continued next page

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100106

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree
A fir, 8" dia., bears N.35°W., 79 lks., mkd: ¼ S36 BT.
Deposit corner stone alongside the iron post.

David Edwards - For: Roseburg Resources - Oct. 2016 - M172-56

Found - 1971 BLM brass capped iron pipe.
A 44" dia. Fir with H.B. bears S.15°W., 11.9'
A 15" Diam. Fir with H.B. bears N.35°W., 52.1'
New BT - 7" dia. Cedar scribed "¼ S36 BT" bears S.88°W, 8.9'
A six foot steel post is set 2 feet north.