

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page 6321)

Set Fir post for cor. to secs. 19, 24, 25 and 30, from which
A Chinquapin 8" dia., bears N.15°E., 12 lks.
A Laurel 10" dia., bears S.55°E., 80 lks.
A Cedar 14" dia., bears S.10°W., 13 lks.
A Fir 18" dia., bears N.18°W., 46 lks.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6226)

Intersect the point for old cor. of secs. 19, 24, 25 and 30, established by references to the SW. and NW. bearing trees as described by the surveyor general; all other traces of the cor. have disappeared. I change this cor. to refer to secs. 24 and 25 only and perpetuate it as follows; at the exact cor. point
Set a basalt stone, 15x10x8 ins., 10" in the ground, marked with 2 notches on S. and 4 notches on N. edge; from which
A Cedar 18" dia., bears S.10°W., 13 lks. dist. mkd. T29S R3W S25 BT.
A Fir 24" dia., bears N.18°W., 46 lks. dist. mkd. T29S R3W S24 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126

Found stone at corner and both BTs as recorded.
Set brass cap alongside corner stone, mkd:
County Surveyors office
S24 | T29S
R3W S25 | R2W
1962

The corner is on steep South slope.

Fd. by Mark Smalley - Oct. 1999 - M 134-8

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2157, Surveyed March/May 2007 - DCSO records Vol. 57 Pages 22551-2

The cor. of secs 24 & 25 only, on the E. bdy. of the Tp., perpetuated by Byron, in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground, with the original stone, 12x12x9", lying alongside, with 5 grooves visible, and a brass cap (properly) mkd. cont.

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100242

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T29-3

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which bearing trees mkd. by Strickler
A cedar, 42" dia., bears S.10°W., 8.6 ft., with a healed blaze.
A fir, 34" dia., bears N.18°W., 28.6 ft., with a healed blaze. (Record, 30.4 ft.)