

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION Sec. cor. for 13 & 24 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6322)

Set Maple post for cor. to secs. 13, 18, 19 and 24, from which

- A Fir 24" dia., bears N.55°E., 7 lks.
- A Fir 18" dia., bears S.53°E., 24 lks.
- A Fir 24" dia., bears S.65°W., 58 lks.
- A Fir 30" dia., bears N.80°W., 26 lks.

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6227)

Apportioned distance.

Set a basalt stone 15x7x6 ins., 10" in the ground for cor. of secs. 13 and 24, T29S R3W only, marked with 3 notches on N. and S. edges; from which

- A Fir 36" dia., bears S.71°W., 186 lks. dist. mkd. T29S R3W S24 BT.
- A Fir 32" dia., bears N.17°W., 257 lks. dist. mkd. T29S R3W S13 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 29, 1957 - C.S. File 42/315-2

Determined by old BTs:

- 40" Fir snag bears S.72½°W., 124.0 ft., found scribe.
- 40" Fir N.16°W., 170.0 ft.
- West ¼ corner sec. 19, T29S R2W, brass cap bears North 13.2 ft.
- At corner point found stone and Set 1¼" x 24" iron pipe, from which
 - 9" Fir bears N.42°W., 19.4 ft. mkd. S13 BT.
 - 8" Fir bears S.67°W., 19.0 ft. mkd. S24 BT.
 - 10" Fir bears S.31°W., 18.0 ft. mkd. S24 BT.
- Creek bears North 14.0 ft. dist.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15837-38)

The cor. of secs. 13 and 24 only, perpetuated and recorded by Markham in 1957, monumented with the original basalt stone 15x7x6 ins., firmly set, projecting 6" above ground, mkd. with 3 grooves on N. and S. faces, alongside of which is an (Cont. Next Page)

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100279

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T29-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

iron pipe, 1¼" dia., firmly set, projecting 10" above ground from which remains of the original bearing trees;

A Fir snag 35" dia., bears S.70°W., 186 lks. dist., with scribe marks T29S R3W BT visible on open blaze. (Rec. S.71°W.)

A Fir 39" dia., bears N.18½°W., 257 lks. dist., with scribe marks 3 BT visible on open blaze. (Rec. N.17°W.)

and bearing trees mkd. by Markham:

A Fir 13" dia., bears S.31°W., 27 lks. dist., with healed double blaze.

A Fir 11" dia., bears S.67°W., 29 lks. dist., with healed double blaze.

A Fir 12" dia., bears N.42°W., 29½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S	T 29 S
S 13	R 2 W
S 24	S 19
R 3 W	
1976	

from which a new bearing tree

A Fir 13" dia., bears S.68 3/4°W., 105 lks. dist., mkd. T29S R3W S24 BT.

Insert iron pipe inside iron post, and deposit corner stone alongside iron post.