

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100379

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6322)

Set Fir post for ¼ sec.cor., from which
A Laurel 8" dia., bears N.75°E., 14 lks.
A Laurel 5" dia., bears S.38°W., 29 lks.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6228)

Apportioned distance
Set a basalt stone 15x8x6 ins., 10" in the ground, for ¼ cor. of sec. 13, T29S R3W only, marked ¼ on W. face; from which
A Fir 18" dia., bears S.28°30'W., 101 lks. dist., mkd. ¼ S13 BT.
A Fir 34" dia., bears N.34°W., 241 lks. dist., mkd. ¼ S13 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-85

Found both original BTs, check OK for bearings and distances, shows scribing and scars.
Set 2"x2"x4 ft. stake at corner, 10.5 ft. South of brass cap for cor to secs. 18 and 19, T29S R2W,
New BTs- 16" R.Fir bears S.53°W., 8.8 ft. scribed ¼ S13 CS BT
18" R.Fir bears N.41°W., 14.5 ft. scribed ¼ S13 CSBT

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15838-39)

The ¼ sec. cor. of sec. 13 only, perpetuated and recorded by Byron in 1962, determined from the remains of the original bearing trees:
A Fir 35" dia., bears S.28½°W., 101 lks., with healed blaze.
A root hole bears N.37°W., 241 lks., with a down Fir alongside, 36" dia., with healed blaze. (Rec. N.34°W.) and bearing trees mkd. by Byron:
A Fir 17" dia., bears S.53°W., 15½ lks. dist., with healed double blaze.
A Fir 23" dia., bears N.48 ¾°W., 22½ lks. dist., with healed double blaze.
At the corner point
(Cont. Next Page)

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100379

PRIMARY CORNER DESCRIPTION East 1/4 Cor. S. 13 only, T29-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground,
with brass cap mkd:

T 29 S
R 3 W | R 2 W
¼ S 13 |
1976

Fd. and used in Subd. of sec. 13 in BLM survey by Dale
Bedell, under Group #1383 - surveyed May/June 1987 - DCSO
records, Vol. 48 Pg. 18379