

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West bdy)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6228)

-----  
Set a basalt stone 18x12x7 ins., 12" in the ground for cor. of secs. 18 and 19, marked with 3 notches on N. and S. edges, from which

A Fir 42" dia., bears N.1°45'E., 263 lks. dist. mkd. T29S R2W S18 BT.

A Fir 24" dia., bears S.32°E., 217 lks. dist. mkd. T29S R2W S19 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew -Dec. 1962 - C.S. File 52/126-85

-----  
Found - Orig. 42" now 48" Fir N.1°45'E., 167.0 ft. (not 173.6 ft.), shows good bark scribing and old scar  
Do not find either corner stone, but both orig. bTs for E. 1/4 Cor. Sec. 13.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S  
R3W | S 18 R2W  
      | S 19  
      1962

New BTs- 12" R.Fir bears S.12½°E., 21.4 ft. mkd. S19 T29S R2W CS BT.

8" R.Fir bears N.87°E., 22.6 ft. mkd. S18 CS BT.

Corner is on steep North slope.

Fd. and used in BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15839)