

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6322)

Set Yew post for cor. to secs. 7, 12, 13, 18, from which
A Laurel 12" dia., bears N.35°E., 10 lks.
A Fir 10" dia., bears S.50°E., 19 lks.
A Fir 10" dia., bears S.12°W., 20 lks.
A Fir 10" dia., bears N.50°W., 17 lks.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 39 Page(s) 6229)

Intersect the old cor. of secs. 7, 12, 13 and 18, which is a badly decayed post, witnessed by the SE. bearing tree as described by the surveyor general, all other traces of the cor. have disappeared. I change this cor. to refer to secs. 12 and 13 only and perpetuate it as follows: alongside the old cor.
Set a basalt stone 18x7x5 ins., 12" in the ground marked with 4 notches on S. and 2 notches on N. edge; from which
A Fir 15" dia., bears S.55°W., 35 lks. dist. mkd. T29S R3W S13 BT.
A Fir 20" dia., bears N.68°15'W., 47 lks. dist. mkd. T29S R3W S12 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-84

Found stone at corner & both BTs, now snags, as recorded, show scribing. Also found brass cap set for West 1/4 S18 R2W, as recorded.
New BTs- 7" R.Fir bears N.74°W., 29.3 ft. mkd. S12 CS BT.
7" R.Fir bears S.58½°W., 42.3 ft. mkd. S13 CS BT.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15840)

The cor. of secs. 12 and 13, perpetuated and recorded by Byron in 1962, monumented with the original basalt stone 18x7x5 ins., firmly set, projecting 4" above ground mkd. with 2 grooves on N. and S. faces, from which the remains of the original bearing trees:
A Fir 23" dia., bears S.50°E., 19 lks. dist., with healed blaze. (Cont. Next Page)

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100439

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13 only, T29-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and the remains of bearing trees mkd. by Strickler:
A Fir snag 18" dia., bears S.55°W., 35 lks. dist. with
fragmentary scribe marks visible on open blaze.
A root crown bears N.68¼°W., 47 lks. dist., with
fragmentary scribe marks visible on open and decayed
blaze.

and bearing trees mkd. by Byron
A Fir 10" dia., bears S.56°W., 64½ lks. dist., with healed
double blaze.
A Fir 9" dia., bears N.75°W., 44 lks. dist., with healed
double blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground,
with brass cap mkd:

T 29 S	T 29 S
S 12	R 2 W
S 13	S 18
1976	

Deposit corner stone alongside iron post.

Tony Hostetter - For: Seneca Jones Tbr Co - 4/2006 - M150-38

Found - 1976 brass cap & accessories as described by J J
Carlson in 1976 (DCSO BLM Recs. Vol 39 Pg 15840)
New BTs- 12" fir, scribed "S13 NE BT", bears S.74°W. 11.5 ft.
to spike.
11" Fir, scribed "S12 SE BT" bears N.53°W., 14.0 ft.
to spike.