

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec Cor for 7 & 18 only, (West bdy)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6230)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 7 and 18, with brass cap mkd.

T29S
S 7
S 18
R2W
1917

from which

A Cedar 12" dia., bears N.17°45'E., 43 lks. dist. mkd. T29S R2W S7 BT.

A Fir 12" dia., bears S.47°15'E., 71 lks. dist. mkd. T29S R2W S18 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-86

Found - Brass cap at corner.

Orig. 12" now 20" Cedar N.21°E., 28.4 ft. (not N.18°E.), shows good scribing and scar.

Orig. SE. BT, now down.

New BT - 12" Yewwood bears S.46°E., 28.0 ft. scribed S18 T29S R2W CS BT.

Fd. Ok by Tony Hostetter 4/2006 - M150-38