

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, (West bdy)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6231-32)

-----  
Set an iron post 3 ft. long, 2" dia., 24" in a rock slide, for cor. of secs. 6 and 7, with brass cap mkd: T29S  
S6  
S7  
R2W  
1917

from which

- A Fir 20" dia., bears N.38°45'E., 96 lks. dist., mkd. T29S R2W S6 BT.
- A Fir 20" dia., bears S.39°30'E., 99 lks. dist. mkd. T29S R2W S7 BT.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15842)

-----  
Point for the cor. of secs. 6 and 7 only, determined by the method of broken boundaries; there is no remaining evidence of the original corner.  
Set an iron post 28" long, 2½" dia., 26" in the ground, with brass cap mkd: T 29 S T 29 S  
R 3 W  $\frac{S 6}{S 7}$   
S 1 R 2 W  
1976

from which

- A Madrone 8" dia., bears N.80°E., 30 lks. dist., mkd. T29S R2W S6 BT.
- A sandstone boulder 15x10x6 ft. above ground, bears S.79½°E., 48½ lks. dist., mkd. X BO on W. face.