

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6292)

-----  
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$   
S7|S8  
1917

from which

A Fir 18" dia., bears N.31°E., 46 lks. dist. mkd.  $\frac{1}{4}$  S8 BT.

A Fir 10" dia., bears S.45°15'W., 40 lks. dist. mkd.  $\frac{1}{4}$  S7 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz; K. Reed; F. Silagy; V. Woodral, crew - July 26, 1979 - C.S. File 60/34-6

-----  
Found - 1" x 36" I.P. with 1917 GLO brass cap, properly mkd. protruding 15" above ground.

18" D.Fir now 28" bears N.31°E., 30.4 ft. with well healed single blaze.

10" D.Fir now 18" bears S.45°W., 25.7 ft. with well healed single blaze.

Set pipe and brass cap deeper in ground stamped "RESET 1979".  
New BTs- 14" I.Cedar scribed " $\frac{1}{4}$  S7 CS BT" in double blaze, bears S.85°W., 22.6 ft.

30" D.Fir scribed " $\frac{1}{4}$  S7 CS BT" in double blaze, bears N.6°W., 37.1 ft.