

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 241100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 5 only, T30-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6201-02) (Duplicate Pg. 6825)

Set a porphyry stone 18x12x6 ins., 12" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which
A Fir 30" dia., bears N.21°W., 10 lks. dist. mkd. ¼ S32 BT
A Madrone 12" dia., bears S.10½°E., 56 lks. dist. mkd. ¼ S5 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6220)

Intersect the ¼ sec. cor., which is a porphyry stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 5, T30S R2W only by destroying all marks referring to sec. 32 and marking ¼ on S. face. From cor.
A Fir 28" dia., bears S.62°W., 70 lks. mkd. ¼ S5 BT. (New BT)
A Madrone 12" dia., bears S.10°30'E., 56 lks. dist. mkd. ¼ S5 BT. (Old BT)