

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 276700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 32 only, T28-2

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5430-31)

Set yew stake, 3 ft. long, 5" sq., 24" in the ground for ¼ sec. cor., marked ¼ S32 on N. face, and dig pits, 18x18x12 ins., E. and W. of cor. and raise mound of earth 3½ ft. base, 1½ ft. high N. of cor.; from which
A Hemlock 36" dia., bears N.13°W., 28 lks. dist., marked ¼ S32 BT.
No other tree fit to mark.

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6235-36)

The ¼ sec. cor., which is a post, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows: alongside the old cor.
Set a granite stone, 14x14x6 ins., 9" in the ground, for ¼ cor. of sec.32, T28S R2W only, marked ¼ on N. face; from which
A Hemlock 36" dia., bears N.11°E., 68 lks. dist., marked ¼ S 32 BT. (New BT)
A Hemlock 36" dia., bears N.13°W., 28 lks. dist., marked ¼ S 32 BT (Old BT)

Survey by John H. Markham, Jr. - Dec. 12, 1961 - C.S. File 51/221-6

Determined by Old BTs
40" Hemlock stump, logged, bears N.11°E., 44.8 ft., found scribe.
40" Hemlock stump, logged, bears N.13°W., 18.5 ft., found scribe.
At corner point, Set 1¼" x 30" axle with flange up, from which
9" Hemlock bears S.47°W., 56.5 ft. mkd. ¼ S32 BT.
14" Hemlock bears S.13°W., 61.0 ft. mkd. ¼ S32 BT.
Road bears East 130 ft. dist.

Fd OK 10/17/2018 by DCSO C.S. File 67/45-25
NAD 83 N 526,164.57 E 4,263,603.76
 Lat: 43°05'02.0" Long: 122°57'44.2"