

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCS0 records Vol. 15 Page(s) 6277)

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$
S17 | S16
1917

from which

A Fir 20" dia., bears S.52°30'W., 76 lks. dist. mkd. $\frac{1}{4}$ S17
BT.

A Fir 36" dia., bears N.48°E., 61 lks. dist. mkd. $\frac{1}{4}$ S16
BT.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden, and L. Heddens - 9/2022 - C.S. File 65/111-18

Found - Brass Cap (properly mkd)
44" Fir, S.52°30'W., 50.2', Healed scar
53" Fir, N.48°E., 40.3', Healed scar
New - 4" D. Fir, West, 20.8', scribed " $\frac{1}{4}$ S17 BT"
52" D. Fir, S.62°E., 4.7' scribed " $\frac{1}{4}$ S16 BT"
Note - Compass decl. 15°E.