

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, (North)

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCS0 records Vol. 15 Page(s) 6236)

-----  
Set a granite stone, 14x10x7 ins., 9" in the ground, for cor. of secs. 4 and 5, marked with 2 notches on W. and 4 notches on E. edge; from which  
A Hemlock 9" dia., bears S.30°30'E., 41 lks. dist., marked T29S R2W S4 BT.  
A Hemlock 6" dia., bears S.48°30'W., 40 lks. dist., marked T29S R2W S5 BT.

Survey by John H Markham, Jr - Dec. 1961 - C.S. File 51/221-3

-----  
Determined by O.B.T.  
12" Hemlock snag, live, bears S.30°E., 27.0 ft.  
At corner point, Set 2" x 30" I.P., from which  
12" Hemlock bears N.66°E., 79.7 ft. mkd. S32 X BT.  
9" Hemlock bers N.45°E., 78.5 ft. mkd. S32 XX BT.  
East end of a 16" metal culvert through dam bears N.59°E., 51.0 ft.  
Road bears West 120.0 ft.  
Corner lies on SW. edge of small lake.