

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCS0 records Vol. 15 Page(s) 6274)

-----  
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S21}{S28}$   
1917

from which

A Fir 40" dia., bears N.65°E., 17 lks. dist. mkd. 1/4 S21 BT  
A Yew 8" dia., bears S.69°45'W., 23 lks. dist. mkd. 1/4 S28 BT.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden, and L. Heddens - 9/2022 - C.S. File 65/111-22

-----  
Found - 1917 Brass Cap (located 5.0' East of North-South Creek) (properly mkd)  
10'x40" Burned Fir snag, N.65°E., 11.2', Visible scribe "1/4"

New - Yew wood to the Southwest, down and rotten  
8" East trunk of 6-prong Maple, S20°E., 12.0', scribed "1/4 S28 BT"  
9" Fir, S.65°W., 15.5', scribed "1/4 S28 BT"

Note - Metal post, East 3.0'  
Compass decl. 15°E.