

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6267-68)

-----  
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$   
S16|S15  
1917

from which

A Fir 36" dia., bears N.27°30'E., 42 lks. dist. mkd.  $\frac{1}{4}$  S15 BT.

A Fir 18" dia., bears N.40°15'W., 94 lks. dist. mkd.  $\frac{1}{4}$ S16 BT.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Page(s) 23943)

-----  
The  $\frac{1}{4}$  sec cor. of secs. 15 & 16, monumented with the original iron post, 1" dia., loosely set & bent over, projecting 10" above ground, with a brass cap mkd.  $\frac{1}{4}$  S16 S15 1917

At the corner point

Straighten and reset the 1917 iron post, 36" long, 1" dia., 31" in the ground, and add marks to the brass cap to now read

T 29 S R 2 W  
 $\frac{1}{4}$   
S 16|S 15  
2019  
1917

from which new bearing trees

A fir, 9" dia., bears S.29°E., 26.7 ft., mkd.  $\frac{1}{4}$  S15 BT.

A fir, 8" dia., bears S.84 $\frac{3}{4}$ °W., 27.6 ft., mkd.  $\frac{1}{4}$  S16 BT.