

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6268)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap marked

T29S	R2W
S9	S10
S16	S15
1917	

from which

- A Fir 12" dia., bears N.43°E., 23 lks. dist. mkd. T29S R2W S10 BT.
- A Fir 22" dia., bears S.56°30'E., 67 lks. dist. mkd. T29S R2W S15 BT.
- A Fir 12" dia., bears S.30°30'W., 30 lks. dist. mkd. T29S R2W S16 BT.
- A Fir 16" dia., bears N.78°45'W., 63 lks. dist. mkd. T29S R2W S9 BT.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Page(s) 23940)

-----  
The cor. of secs. 9, 10, 15 and 16, monumented with the original iron post, 2" dia., firmly set, projecting 16" above ground, in a collar of stone, with a brass cap (properly) mkd from which the remains of a BT mkd. by person(s) unknown

A decayed fir stump, 19" dia., bears N.50½°E., 8.5 ft., with scribe marks T2 visible on a partially opened blaze.

and new bearing trees

- A fir, 9" dia., bears N.44¾°E., 12.5 ft. mkd. T29S R2W SW BT and a Mag Nail at the base on left side center.
- A fir, 16" dia., bears S.4¾°E., 34.8 ft., mkd. T29S R2W S15 BT.
- A fir, 12" dia., bears N.89¾°W., 6.8 ft., mkd. X BT.
- A fir, 12" dia., bears N.63¾°W., 21.1 ft., mkd. T29S R2W S9 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.