

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6269)

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$
S9 | S10
1917

from which

- A Fir 12" dia., bears S.28°W., 32 lks. dist. mkd. $\frac{1}{4}$ S9 BT.
- A Fir 16" dia., bears S.75°E., 35 lks. dist. mkd. $\frac{1}{4}$ S10 BT

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Page(s) 23940)

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with the original iron post, 1" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which new bearing trees

- A fir, 12" dia., bears N.66 $\frac{1}{2}$ °E., 22.9 ft., mkd. $\frac{1}{4}$ S10 BT.
- A hemlock, 15" dia., bears S.39°W., 27.1 ft., mkd $\frac{1}{4}$ S9 BT.