

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6269-70)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 3, 4, 9 and 10, , with brass cap marked

T29S	R2W
S4	S3
S9	S10
1917	

from which

- A Balsam Fir 12" dia., bears N.38°E., 62 lks. dist. mkd. T29S R2W S3 BT.
- A Fir 12" dia., bears S.18°E., 46 lks. dist. mkd. T29S R2W S10 BT.
- A Fir 12" dia., bears S.22°W., 44 lks. dist. mkd. T29S R2W S9 BT.
- A Fir 15" dia., bears N.56°W., 32 lks. dist. mkd. T29S R2W S4 BT.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Pages 23940-1)

-----  
The cor. of secs. 3, 4, 9 and 10, monumented with the original iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

- A fir stump, 12" dia., bears S.18°E., 30.4 ft., with a healed blaze.
- A fir stump, 14" dia., bears S.22°W., 29.0 ft., with a healed blaze.

and new bearing trees

- A fir, 9" dia., bears N.43°E., 19.2 ft. mkd T29S R2W S3 BT
- A fir, 12" dia., bears S.25¾°E., 9.8 ft., mkd. T29S R2W S10 BT.
- A fir, 6" dia., bears S.48¼°W., 4.6 ft., mkd. X BT.
- A fir, 23" dia., bears N.13¼°W., 9.3 ft mkd T29S R2W S4 BT

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.