

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6263)

-----  
Set an iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 sec. cor., with brass cap mkd: 1/4  $\frac{S27}{S34}$   
1917

from which  
A Fir 24" dia., bears S.33°30'W., 42 lks. mkd. 1/4 S34 BT.  
A Fir 20" dia., bears N.46°30'W., 109 lks. mkd. 1/4 S27 BT.

Douglas Co. Surveyors Office - Clell Goodwin; Vic Cangie - Sept. 22, 1975 - C.S. File 57/36-8

-----  
Found - 1917 GLO brass cap on a 1" x 30" Iron pipe, stamped properly.  
Orig. 20" now 24" Fir, bears N.46½°W., 71.9 ft.  
Orig. SW. BT, a 24" Fir is blown down.  
New BT - 7" Fir scribed "1/4 S34 CS BT" in a double blaze bears S.25½°W., 17.6 ft.

Mark Smalley, for Scott Timber Co. Nov. 1997 - M 124-68

-----  
Found - 1917 GLO brass cap on iron pipe  
New Accessories -  
7" Fir, N.12°E., 8.7 ft. scribed "1/4 S BT"  
8" Fir, S.58°W., 45.4 ft. scribed "1/4 S BT"  
13" Fir, N.89°E., 8.6 ft. scribed "1/4 S BT"  
12" Fir, S.71°E., 12.7 ft. scribed "1/4 S BT"

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 9/24/2020 - C.S. File 67/46-42

-----  
Found OK  
Found - Unrec. 24" Fir, N.52°E., 4.2 healed high low blz new side center nail.  
Lat: 43.019303360 Long: -122.932136391