

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Elmer F Strickler, US Transitman, under Special Instructions dated Jan 22, 1917 - (DCSO rec Vol. 15 PG) 6267)

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{l} S15 \\ S22 \\ 1917 \end{array}$

from which
 A Fir 12" dia., bears N.26°E., 10 lks. mkd. $\frac{1}{4}$ S15 BT
 A Fir 18" dia., bears S.11°30'W., 46 lks. mkd. $\frac{1}{4}$ S22 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - June 28, 1967 - C.S. File 54/58-1

Found - 1917 GL0 brass cap in good condition and properly marked.
 18" now 20" Fir stump S.11½°W., 30.4 ft. Open and find partial "BT" scribe and reverse.
 Stump only for NE. BT.
New BTs- 40" D.Fir stump, S.58°W., 22.5 ft. mkd. $\frac{1}{4}$ S22 CS BT
 8" Yew snag, N.13°E., 26.1 ft. mkd. $\frac{1}{4}$ S15 CS BT.
This corner lies in approx. middle of logged off unit on SW. slope.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Pages 23938-9)

The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, perpetuated by the Douglas County Surveyors Office, in 1967, monumented with the original iron post, 36" long, 1" dia., loosely set, and bent, projecting 8" above ground, with a brass cap mkd. $\frac{1}{4}$ S15 S22 1917 from which the remains of an original bearing tree
 A decayed fir stump, size indeterminate, bears S.11½°W., 30.4 ft., no marks visible.
and the remains of the BTs mkd. by the Douglas Co. Surveyor's Office
 A roothole bears N.10¾°E. 26.8 ft alongside of which is a downed yew snag, size indeterminate, no marks visible.
 A decayed fir stump, size indeterminate, bears S.58¾°W., 21.3 ft., no marks visible.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. $\frac{1}{4} \begin{array}{l} T29S R2W \\ S15 \\ S22 \\ 2019 \end{array}$

continued next page

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees
A fir, 16" dia., bears S.76½°W., 28.7 ft., mkd. ¼ S22 BT.
A fir, 15" dia., bears N.21¾°W., 12.5 ft., mkd. ¼ S15 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each monument.

Deposit the original iron post alongside the stainless steel post.