

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 440440

PRIMARY CORNER DESCRIPTION Center 1/4 Sec 15

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Pages 23941-2)

Point for the center ¼ sec. cor. of sec. 15, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 29 S R 2 W
C ¼ S 15
2019

from which

A fir, 13" dia., bears S.73¼°W., 14.8 ft., mkd. C¼ S15 BT.

A fir, 8" dia., bears N.10¼°W., 13.5 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.