

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6269)

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S10}{S15}$
1917

from which

A Balsam Fir 14" dia., bears S.48°W., 25 lks. dist. mkd. $\frac{1}{4}$ S15 BT.

A Hemlock 15" dia., bears N.66°E., 44 lks. dist. mkd. $\frac{1}{4}$ S10 BT.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Page(s) 23939)

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with the original iron post, 1" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd.

from which new bearing trees

A fir, 16" dia., bears S.0 $\frac{1}{4}$ °E., 9.5 ft., mkd. $\frac{1}{4}$ S15 BT.

A fir, 16" dia., bears N.18°W., 3.3 ft., mkd. $\frac{1}{4}$ S10 BT.