

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6216)

Set a basalt stone 18x12x4 ins., 12" in the ground for cor. of secs. 34 and 35, marked with 2 notches on E. and 4 notches on W. edge; from which
A Fir 24" dia., bears N.32°30'E., 57 lks. dist., mkd. T29S R2W S35 BT.
A Fir 40" dia., bears N.12°30'W., 47 lks. dist. mkd. T29S R2W S34 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-48

Found - Stone at sec. cor. mkd. 2 notches on E. & W.
40" now 45" D.Fir N.12½°W., 31.0 ft. shows good scar.
24" Fir now stob, N.32½°E., 37.6 ft. scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R2W S 34 | S 35
T 30 S 1968 S 3
New BTs- 16" Hemlock N.8°E., 26.6 ft. mkd. T29S R2W S35 CS BT
14" Hemlock S.51½°W., 33.9 ft. mkd. T30S R2W S3 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 2/10/98 - C.S. File 64/79-27

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 13" above ground. 1968
18"x12"x4" stone found loose on top of ground 2 ft. West of BC/IP. Stone is marked on two sides, 2 hashes on one side and 4 on its opposite. Orig. stone.
40" now 44" dia., 2 ft. high D.Fir stump, bears N.12½°W., 31.0 ft. (Agrees with rec.) OBT
Orig. NE BT now gone.
16" now 17" dia., 3 ft. high Hemlock stump with scribing visible on a partially healed blaze "35 CS" bears N.8°E., 26.6 ft. (Agrees with rec.) 1968
1968 SW BT gone.
DCSO BC/IP mkd: T29S R2W S35/S3 | S2 T30S bears East 32.0 ft. (Rec. East 33.7 ft.)
Set - Stone placed loose along west edge of BC/IP.
(Cont. next page)

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. 34 & 35 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

8" dia., D.Fir, double blazed and scribed "T29S
R2W S35 CS BT" bears N.19°E., 15.0 ft.
7" dia., D.Fir, double blazed and scribed "T29S
R2W S34 CS BT" bears N.53°W., 25.3 ft.
Note - Metal caps are on BT stumps. See sketch in file.