


PRIMARY CORNER DESCRIPTION Sec Cor for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6252-53)

 Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 26, 27, 34 and 35, with brass cap marked:



from which

- A Fir 10" dia., bears N.63°E., 78 lks. mkd T29S R2W S26 BT
- A Fir 24" dia., bears S.34°E., 46 lks. mkd T29S R2W S35 BT
- A Fir 24" dia., bears S.17°W., 61 lks. mkd T29S R2W S34 BT
- A Cedar 10" dia. bears N.29°W., 98 lks mkd T29S R2W S27 BT

Douglas Co. Surveyors Office - Clell Goodwin; Vic Cangie, crew - Sept. 22, 1975 - C.S. File 57/36-11

 Found - 1917 GLO brass cap, properly stamped, projecting 8" out of the ground and apparently undisturbed.
 An Orig. 24" now 38" Fir bears S.34°E., 30.4 ft.
 Orig. 10" now 16" Cedar bears N.29°W., 65.4 ft. (call N.29°W., 64.7 ft.)
 Orig. 24" Fir now a rotted stump, bears S.17°W., 40.8 ft. (Call S.17°W., 40.3 ft.)
 No sign of orig. NE. BT, which has been removed by road construction.
 New BTs- 13" Fir scribed "T29S R2W S34 CS BT" in a double blaze, bears S.15½°W., 27.5 ft.
 12" Cedar scribed "T29S R2W S26 CS BT" in a double blaze, bears N.72½°E., 21.1 ft.

Mark Smalley, for Scott Timber Co. Nov. 1997 - M 124-68

 Found - 1917 GLO brass cap on iron pipe.
 22" Cedar, N.73°E., 21.9 ft. healed, no record
 14" Cedar, N.32°E., 23.8 ft. snag, no record
 24" Fir, S.34°E., 30.4 ft. stump
 24" Fir, S.17°W., 40.3 ft. healed
 34" Cedar, N.29°W., 64.7 ft. healed
 New - 12" Cedar, N.86°W., 14.6 ft. scribed "S27 BT"
 12" Fir, N.18°E., 13.8 ft. scribed "S26 BT"

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 9/24/2020 - C.S. File 67/46-41

 Fd Ok
 Lat: 43.019288031 Long: -122.922263691